



DECLARATION OF PERFORMANCE

No. 1 DOP - Alka 145

Type	Alka 145
Intended use of the product	For reinforcement of cement based renderings
Producer	ALLIANZ TC COM SRL Romania,Ciorogarla,Sat Darvari
System of assessment and verification of constancy of performance of the construction product	System 2+
Technical assessment body	Technical and test Institute for Construction Prague Issued ETA 21/0927

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Organic content %	21 ± 2	EAD 040016-01-0404
Mesh opening (warp-weft)mm	(4.2*4.7) ±0.5	
Tensile strength in the as-delivered state N/mm (warp/weft)	≥36 / ≥ 45	
Elongation(%) in the as-delivered state % (warp/weft)	≤4.5	
Tensile strength after alkalis conditioning N/mm (warp/weft)	≥23 / ≥ 38	
Elongation(%) after alkalis conditioning (warp/weft)%	≤3	
Mass per area gr/m ²	145±5%	
Roll width mm	NPA	
Thickness , mm	0.5±0.2	
Mass per area gr/m ²	145±5%	
Roll width mm	1000(+1%-0%)	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of the performance is issued, in accordance of Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by :

Darvari , 20.01.2023

.....
Tache Alexandru , product manager

PROCREDIT BANK S.A.
 RO88 MIRO 0000 0700 2138 0501 (RON)
 RO88 MIRO 0000 1100 2137 0702 (USD)
 RO23 MIRO 0000 0700 2138 0604 (EUR)